

A New Technique for Modeling Land Subsidence Facilitates Better Groundwater Management

Overview

Land subsidence – the sudden sinking or gradual settling of Earth’s surface – can occur naturally or be triggered by human activity. One of the most common human-affected factors is groundwater pumping, a practice that has been steadily increasing due to prolonged periods of drought. Groundwater pumping is so prevalent in some areas that it is severely compromising the quantity and quality of the groundwater as well as the physical structure of the land and aquifer capacity beneath it. Large-scale initiatives for putting water back into the ground, or groundwater recharge, are being implemented in some regions. However, groundwater resource managers still need better information to determine where the land is at greatest risk of subsidence as well as where recharge efforts would be the most effective. Integrating two reliable data gathering sources – helicopter-deployed systems (airborne electromagnetic or AEM technology) that measure electromagnetic fields and satellite-deployed systems (interferometric synthetic aperture radar or InSAR) to measure deformations – offers groundwater managers an improved method for more accurately modeling changes in the land surface related to the pumping and recharge of groundwater. Additionally, the ability to more precisely detect subsidence may offer an early warning system for declining groundwater levels.

Problem Statement

A single data-gathering method that provides a reliable and complete picture of the conditions above and below the surface of the land is currently unavailable. Not having this information creates challenges for developing accurate, predictive subsidence models which resource managers need to make optimal decisions for groundwater management to prevent further disturbance of the land and underground aquifers.

The Facts

In the United States, the U.S. Geological Survey (USGS) estimates that more than 17,000 square miles of land across 45 states have been directly affected by subsidence. It’s particularly problematic throughout the Central Valley of California, where years of severe drought combined with heavy agricultural extraction of groundwater have resulted in areas marked by up to 28 feet of subsidence. Effects of subsidence include: the loss of groundwater storage; damage to levees and other infrastructure; and potential water contamination due to the drainage of clays and the resulting concentrations of naturally occurring chemicals like arsenic.

In an effort to avoid further aggravating existing issues of subsidence, water agencies and farmers are already exploring novel ways to capture water run-off and put it back into the groundwater system. However, the required infrastructure is often costly, so having access to accurate prediction models on the impact of recharge efforts in specific locations would help administrators better manage their water resources and optimize their investments.

To date, decision-makers have largely relied upon data gathered from three sources: monitored water wells that only assess a portion of the aquifer; GPS which is labor intensive and can be subject to error; or the satellite data that measure surface changes. By developing a new and accurate model that accounts for deformation of the subsurface layers through the combination of two consistent, yet distinct, measuring techniques, a more comprehensive understanding of actual subsurface conditions can be formed and a predictive capability developed.

The Challenges

Traditional approaches for modeling subsurface conditions have generally relied upon data obtained from monitored wells and more recently, satellite and GPS data. The datasets required to implement the new approach do exist, however, there is a lack of knowledge on how to properly combine and analyze them to obtain the information needed to make accurate predictions.

- Satellite data (InSAR) offers a promising technology that can map large areas of land with a high level of accuracy and resolution, but measurements of changes observed at the surface do not provide users with a complete picture of subsidence.
- Airborne electromagnetic Aerial (AEM) data offers a three-dimensional look at the surface. However, it only supplies part of the information needed to fully understand the scope of subsidence.
- The new hybrid approach developed here relies upon having sufficient satellite and AEM data available for the specific area of subsidence under review as well as trained staff who can execute the computations. And as scenarios change for each case study, the resulting approach likely requires adoption by a large federal or state agency to ensure data are collected properly and stored under open access guidelines.

This brief is based on research and findings by Rosemary Knight, The George L. Harrington Professor in the School of Earth Sciences at Stanford University and Ryan Smith, now with the Department of Geosciences and Geological and Petroleum Engineering, Missouri University of Science and Technology

FOR MORE INFORMATION

Office of External Affairs
Stanford Woods Institute for the Environment

woods-extaffairs@stanford.edu

woods.stanford.edu

The Recommendations

Methods to better predict subsidence and prioritize areas likely to benefit from managed aquifer recharge (MAR) to minimize subsidence while preventing loss of storage capacity are urgently needed. The hybrid InSAR/AEM method developed here can be used to predict subsidence under a variety of pumping/recharge scenarios and provide groundwater managers with a useful oversight tool, but for InSAR/AEM to be more widely used the following is necessary:

- Increase the collection and compilation of both types of remote sensing data across the state of California and other groundwater depleted regions where subsidence is an issue. Access to these data sets would allow for more agricultural regions to be monitored regularly and at relatively lower cost.
- Develop a computational tool or dashboard that integrates the two datasets into one model. Upscaling the technology permits groundwater managers to predict susceptibility to subsidence conditions, have confidence in proposed MAR projects, and develop plans that strategically utilize available recharge water.
- Promote the wide range of benefits from combining InSAR and AEM data along with a computational tool to local water managers and agencies, agricultural and other community stakeholders. Successfully integrating these two forms of data will provide a new way to link subsidence to groundwater models, critically needed to support sustainable management plans in areas at risk for subsiding as well as drinking water contamination from over-pumping.

ABOUT THE AUTHOR



Rosemary Knight

Rosemary Knight is the George L. Harrington Professor in the School of Earth, Energy & Environmental Sciences; and affiliated faculty at the Stanford Woods Institute for the Environment.